

Producto	Amp.	Polos	24V	110 / 130V	220 / 240V	380 / 440V	600V	Hasta 500Hz									
Toma de sobreponer IP 44  Opción rosca GAS(*) Sección del conductor (mm ²) <table border="1" data-bbox="690 476 1150 714"> <thead> <tr> <th>Amp.</th> <th>16A</th> <th>32A</th> </tr> </thead> <tbody> <tr> <td>Mín.</td> <td>2,5</td> <td>4,0</td> </tr> <tr> <td>Máx.</td> <td>4,0</td> <td>6,0</td> </tr> </tbody> </table> 	Amp.	16A	32A	Mín.	2,5	4,0	Máx.	4,0	6,0	16	3	S-3002	S-3004	S-3006	S-3009	S-3005	S-3000
	Amp.	16A	32A														
	Mín.	2,5	4,0														
	Máx.	4,0	6,0														
	16	4	S-4002	S-4004	S-4009	S-4006	S-4005	S-4000									
	16	5	S-5002	S-5004	S-5009	S-5006	S-5005	S-5000									
	32	3	S-3202	S-3204	S-3206	S-3209	S-3205	S-3200									
	32	4	S-4202	S-4204	S-4209	S-4206	S-4205	S-4200									
	32	5	S-5202	S-5204	S-5209	S-5206	S-5205	S-5200									
16	7				S-100-6												
32	7				S-127-6												

(*) para rosca Gas verificar tabla de adaptadores