



Producto		Amp.	Polos	24V	110 / 130V	220 / 240V	380 / 440V	600V	Hasta 500Hz										
Toma de sobreponer negativa (macho) 	IP 44 	Sección de los contactos (mm <sup>2</sup> ) <table border="1" data-bbox="927 580 1528 890"> <thead> <tr> <th>Amp.</th> <th>16A</th> <th>32A</th> </tr> </thead> <tbody> <tr> <td>Mín.</td> <td>2,5</td> <td>4,0</td> </tr> <tr> <td>Máx.</td> <td>4,0</td> <td>6,0</td> </tr> </tbody> </table>	Amp.	16A	32A	Mín.	2,5	4,0	Máx.	4,0	6,0	16	3	SN-3002	SN-3004	SN-3006	SN-3009	SN-3005	SN-3000
	Amp.		16A	32A															
	Mín.		2,5	4,0															
	Máx.		4,0	6,0															
	Opción rosca GAS(*)		16	4	SN-4002	SN-4004	SN-4009	SN-4006	SN-4005	SN-4000									
			16	5	SN-5002	SN-5004	SN-5009	SN-5006	SN-5005	SN-5000									
			32	3	SN-3202	SN-3204	SN-3206	SN-3209	SN-3205	SN-3200									
	32	4	SN-4202	SN-4204	SN-4209	SN-4206	SN-4205	SN-4200											
	32	5	SN-5202	SN-5204	SN-5209	SN-5206	SN-5205	SN-5200											